



180mm, Spindle Thread M14 X 2, 2400W, 8,500rpm, 5.9Kg

180mm, Spindle Thread M14 x 2, 2,600W, 8,500rpm, 5.1Kg

G 23SF2

230mm, Spindle Thread M14 x 2, 2,000W, 6,600rpm, 4.3Kg

230 mm, Spindle Thread M14 x 2, 230mm, Spindle Thread M14 x 2, 2,000W, 6,600rpm, 5.1Kg 2,200W, 6,600rpm, 5.1Kg

14,000rpm, Orbit 28,000rpm, 1,1Kg

G 23SW2

G 23SC3 230mm, Spindle Thread M14 x 2, 2,300W, 6,600rpm, 5.0Kg

SV 13YA

Precise grinding,

Max Collet chuck 6mm, 520W, 29,000rpm, 1.7Kg S 15SB Vertical type

705W, 4,500rpm, 2.0Kg

150mm, Spindle Thread M16 x 2,

SAT 180

180mm 2 Speed Sanding & polishing, Spindle Thread M14 x 2, 750W, 1,900rpm/ 3,400rpm, 2.9Kg

SP 18VA 180mm, Spindle Thread

M14 x 2. Electronic control. 1,250W, 0-3,400rpm, 2,8Kg

With dust bag Pad size 92X184mm, 180W, Spindle 10,000rpm, Orbit 20,000rpm, 1,3Kg

FSV 10SA

SV 12SG 114mm with dust bag Pad size 110X100mm, 200W. Spindle

Variable speed Sanding paper & pad size 125mm, Orbital dia 3,2mm, 230W, 7,000-12,000rpm, 1.4Kg

SV 13YB 🥞

Sanding paper & pad size 125mm, Orbital dia 3,2mm. 230W, 12,000rpm 1.4Kg

SB 8V2 🚿 Variable speed Belt size

76X533mm, 1,020W, No load speed 250-450rpm, 4.3Kg

C 7SS

Blade dia 190mm, Max cut. Depth 68mm @ 90° & 46mm @ 45°, 1,050W, 5,500rpm, 3.4Kg C 7ST

Blade dia 185mm, Max cut. Depth 60mm @ 90° & 47mm @ 45°, 1,710W, 5,800rpm, 4.6Kg

235mm, Max cut. Depth 86mm @ 90° & 65mm @ 45°, 2,000W, 5,200rpm, 7.0Kg

C 8FSHE Blade dia 216mm, Compound Miter 45° & Bevel 45° - 45 x 220mm, 1,050W, 5,500rpm, 14.5Kg

C 10FCE2 Blade dia 255mm.

Compound Miter 45° & Bevel 45° - 45 x 102mm, 1,520W, 5,000rpm, 11.9Kg

Blade dia 305mm, Compound Miter 45° & Bevel 45° - 45 x 140mm, 1,520W, 4,000rpm, 19.0Kg

C 12LCH Blade dia 305mm, Compound Miter 45° & Bevel 45° - 40 x 140mm, 1,520W, 4,000rpm, 19.5Kg

FCJ 65V3 Variable speed Wood 65mm Steel plate 6mm, 400W,

Base Tilt angle 45° Right / Left,

0-3,000rpm, 1.5Kg

CJ 90VST Variable speed Wood 90mm, Steel plate 8mm, Base Tilt angle 45° Right / Left, 705W, 850-3,000rpm, 2.2Kg

CJ 160V 160mm, 800W, Length of Stroke 26mm, **CR 13V2** Variable speed Pipe 130mm, Steel plate 19mm, Length of Stroke



CS 40Y Front and Rear Handles with Soft Grip, Bar size: 400mm, 2,000W, Chain Speed: 14.5m/s, 5.5Kg





CM 12Y Wheel dia 305mm, Max cut. Depth 100mm, 2,400W,

5,000rpm with Soft start, 11.5Kg

CC 14STA 355mm, Bar dia-65mm,

Pipe dia 125mm, 2000W, 3900rpm, 14.1 Kg



CC 14STDU 355mm, Bar dia- 65mm, Pipe dia 130mm, 2200W, 3800rpm, 17.0Kg

800-2,800rpm, 2.5Kg



29mm, 1,010W, 0-2,800rpm, 3,3Kg









AUTO Mode 6,000-20,000rpm/15,000-20,000, 1.5Kg



In Steel 1.6mm Stainless 1.2mm, 400W, 4,700rpm, 1.7Kg



Dust Extracting

Orbit Action



Carry Case

079 - 2685 8008

011 - 4752 8944

98360 92333



LOWHIGH



CN 16SA Cutting cap. In Steel 1.6mm Stainless 1.2mm, 400W, 2,300rpm, 1.6Kg













EC 68

- **4**

UM 16VST2 Max Stirrer Diameter-160mm,

300-650rpm/150-300rpm,

RH 600T 200V-240V, 2,000W, 2 Heat settings: 250/500°C & 450-600°C, 0.57Kg



RH 650V 200V-240V, 2, 000W, LCD Display with temp. Buttons, 5 Stage switch: 50-650°C, in increments of 10°C, 0.79Kg

Hose length 10m, 8.3Kg

Induction motor, 1.5hp, 24L, 8bar, 28Kg

BRANCHES: AHMEDARAD

Eco-Products

BANGALORE 080 - 4117 0777 **HYDERABAD** 040 - 4013 8207 022 - 2775 8814 MUMBAI KOLKATA 033 - 2479 7542 BHUBANESHWAR 91- 98302 00254 COCHIN 95677 61040 **JAIPUR** 88240 99593 LUCKNOW 90267 53265 LUDHIANA 85910 91138 PUNE 97027 86342 044 - 2432 8681 / 2435 0111 CHENNA

For any Customer Support / Service **Toll Free Number** 18005725726

Timings: 10am to 6pm Closed on Saturdays / Sundays and Public holidays.

GUWAHATI **HEAD QUARTERS:**

DELHI

Shinagawa Intercity Tower A, 20th floor, 15-1, Konan 2-chrome, Minato-ku, Tokyo 108-6020, Japan. Tel: +81-3-5783-0601 Fax: +81-3-5783-0709



1600W, 5.6Kg

B 16RM Laser guide, Chuck 16mm, 12 Stage speed: 250-3.100rpm, 750W, 75Kg

1,400W, Max, Pressure

100bar, Max. Water discharge: 5.5L/Min, Hose length 5m, 5.4Kg AW 130 1,600W, Max, Pressure 130bar, Max. Water discharge: 6L/Min,

AW 150 2,000W, Max, Pressure

150bar, Max. Water discharge: 6.67L/Min, Hose length 10m, 12.4Kg

Registered & Head Office: Hikoki Power Tools India Pvt. Ltd. Plot No.9A, 1st Phase, Peenya Industrial Area, Bengaluru 560 058. India, Tel: 080 - 4117 0777 / 78 / 2839 6198 Fax: 080 - 4117 1222 Email: ho.mktg@hikoki-powertools.in Website: www.hikoki-powert (Formerly known as **Hitachi Koki India Private Limited**)

POWER TOOLS

2020 - 2021

HiKOKI

UNLEASH the NEXT

Customer Support No. - 18005725726

= (n) <u>-</u>

DB 3DL2

21-Stage torque, 3.6V, 1.5Ah, 6.35mm hex bit shank, Max Lock torque: 5Nm, 0-600rpm, 0-200rpm, 0.45Kg 투기구부터상 **ୖ** ଶ ଶ ଶ ଶ ଶ

DB 10DL

21-Stage torque, 10.8V. 1.5Ah, 6.35mm hex bit shank, Max Lock torque: 10Nm, 0-400rpm, 0.8Kg



0-350rpm, 1.0Kg

angled or straight

DS 12DA 0.8-10mm, 10.8V, Torque - 36Nm, 21-Stage Torque, 12V PEAK battery, No Load speed: 0-1,300rpm, 2.5Ah, 10mm, Max lock Torque: 38Nm, 0-1,400rpm, 0-350rpm, 1.1 Kg

bittes? Olemoe DS 14DFL

22-Stage torque, 14.4V, 1.5Ah, 12mm, Max Lock torque: 47Nm, 0-1,200rpm, 0-400rpm, 1.6Kg



2.0 -13mm, 14.4V, Max Lock torque: 47Nm, 0-1,250rpm, 0-400rpm



G 14DSL

115mm, 14.4V 3.0Ah 9,300rpm, 1.7Kg



Max Lock torque: 53Nm, 0-1,250rpm, 0-450rpm, 1.7Kg

DV 12DA 0.8-10mm, 12V PEAK battery, 2.5Ah, 10mm, Max lock Torque: 38Nm, 0-1,400rpm, 0-350rpm, 1.2Kg DV 14DJL

2.0-13mm, 14.4V, Max Lock torque: 50Nm, 0-1,400rpm, 0-350rpm, 7.0Kg WH 7DL

Equipped with white LED light 7,2V, 1.5Ah, 6.35mm, Max torque 25Nm, 0-2400rpm, 0.58Kg

Ø|@|@|<u>=</u>|`` WH 10DAL

납하는

10.8V, 1.5Ah, 6.35mm Hex Bit Shank, Max torque 108Nm, 0-2,700rpm 1.0Kg

DH 28PCY

SDS-Plus, Concrete: 28mm

850W, 3.4J, 0-1,100rpm, 2.9Kg

Steel: 13mm, 3 Modes,



10.8V, 6.35mm Hex Bit Shank, Max Torque - 105Nm. 0-2,300rpm, 0.9Kg

∅(0) (0) (0) (0) WH 12DA 6.35mm hex bit shank, 12V PEAK battery, 2.5Ah, 10mm, Max lock Torque: 110Nm.

0-2,700rpm, 0-3200rpm, 1.1 Kg

D 10VST

WH 18DBDL2 18V. 6.35mm Hex Bit Shank. Max torque 160Nm, 0-900/1,400/2,000/2,600rpm, 1.7Kg

WR 14DSDL 10-16mm, 14.4V, 235Nm 12.7mm Square bit shank, 0-2,600rpm, 1.6Kg



WR 18DHL

Bolt: 12-22mm, 18V 3.0Ah, 480Nm, 1/2" Square bit shank, 1,500rpm, 3.4Kg

WR 18DSHL

Bolt: 12-22mm, 18V 3.0Ah, Slide type, 480Nm, 1/2" Square bit shank, 1,500rpm, 3.4Kg

∅@@<u>=</u> 🗀 DH 14DSL

> SDS-Plus, Concrete: 16mm, Steel: 13mm, 2 Mode, 14.4V 3.0Ah, 0-1,500rpm, 0-750rpm, 2.1Kg

D 6SH 0.5-6.5mm, 240W, 4.500rpm, 0.9Kg

10mm, 450W, 0-3000rpm, 1.3Kg

D 10VSTA

10mm, 450W, 0-3,200rpm, 1.2Kg

D 13VH 1.5-13mm, 690W, 0-3,000rpm, 0-1,000rpm, 1.9Kg 0-3000rpm, 1.7 Kg

DV 10VST 1.5-10mm, Variable speed, 550 W,

Tool Kit

10mm Impact drill DV 10VST. Twist drill-3. Wood flat bit-2, Masonry drill-3, Wood drill-3, Flathead 50mm-2, Cross Point 50mm-3, Star Shape 50mm-2, T shaped 50mm

DH 26PC

SDS-Plus, Concrete: 26mm,

830W, 3.2J, 0-1,100rpm, 2.8Kg

Steel: 13mm, 3 Modes,

DV 13VSS

1.5-13mm, Variable speed, 550W, 0-2,900rpm, 1.4Kg

Tool Kit

DH 28PBY

SDS-Plus, Concrete: 28mm

850W, 3.4J, 0-1,100rpm, 2.9Kg

Steel: 13mm, 2 Modes,

13 mm Impact drill DV13VSS-1, Masonary bits-4, Steel Bits (HSS)-3, Brad Points (wood drill)-2, Socket 1/4" -9, Plier (combination plier)-8, 25mm Insert Bits-10



VTP 18 18mm 2 speed 640W, 28,600ipm, 17,800ipm 0-1,800rpm, 0-1,050rpm, 2,3Kg

DH 22PBS SDS-Plus, Concrete: 22mm, Steel: 13mm, 2 Modes, 620W, 2.2J, 0-1100rpm, 2.8Kg

DH 24PG SDS-Plus, Concrete: 24mm, Steel: 13mm, 2 Modes, 730W, 2.7J, 0-1,050rpm, 2.7Kg

DH 24PH SDS-Plus, Concrete: 24mm, Steel: 13mm, 3 Modes, 730W, 2.7J, 0-1,050rpm, 2.7Kg

-----**DH 26PB**

SDS-Plus, Concrete: 26mm, Steel: 13mm, 2 Modes, 830W, 3.2J, 0-1,100rpm, 2.8Kg



□□■ 2006 H 65SB3

Strong demolition power,

30mm hexagon, 1,340W, 1,400ipm, Impact force 42J, 16.5Kg

IF DESIGN UVP H 90SG 28.5mm Hexagon. -Bit with Strong Demolition Power, 1,000ipm, 2,000W, Impact force 70J, 32.0Kg W 6VA4 6mm drywall & self-drilling screw with depth stop,

620W, 0-3,000rpm, 1,4Kg

WR 16SE 12mm-22mm, 12-16mm, 370W *3. 1.600/1.400/1. 300/1,100rpm, 360Nm, 2.5Kg 1100W, 620rpm, 7.1Kg **WR 22SE** 800W, M14mm-24mm, 1,400rpm, 620Nm, 4,6Kg

CARRY THE PARTY OF THE PARTY OF

DH 40MC

Drill Bit 40mm, Core Bit 105mm, **WR 25SE** 900W, 22mm-30mm, 22mm-24mm, 1,100rpm, 1.000Nm. 7.7Kg





FHB

SDS-Max, 45mm, 125mm, 1,500W,

120-310rpm, 1,200-2,950ipm, 9.0Kg

SDS-Max, 1,250W,

DH 52ME



FIHB

SDS-Max, 52mm, 160mm, 1,500W,

110-280rpm, 1,000-,400ipm, 11,0Kg

PH 65A Heavy blow chipping 30mm Hexagon, 1,240W, 1,400ipm, Impact force 39.5J, 15.0Kg

SDS-Max, 1,150W, 1,430-2,850ipm, Impact Energy 13.5J, 7.0Kg

H 45ME

G 18SW2

SDS-Max, 1,500W, 1,500-2,100ipm, Impact Energy 26.5J, 11.6Kg

H 60ME



100mm. Spindle Thread M10 x 1.5.

600W, 11,500rpm, 1.7Kg

PDA-100M 100mm, Spindle Thread M10 x 1.5, 715W, 12,000rpm, 1.5Kg



10,000rpm, 2.8Kg

100mm, Spindle Thread M10 X 1.5, 900W, 10,500rpm, 1.8Kg

G 10SN2





125mm, Spindle Thread M14 x 2, 715W, 10,000rpm, 2.1 Kg



125mm, Spindle Thread M14 x 2, 730W, 10,000rpm, 1.8Kg



12,000rpm, 2,3Kg



125mm, Spindle Thread M 14X2, 125mm, Spindle Thread M14 x 2, 1,400W. 900W, 10,500rpm, 2.0Kg 11,500rpm, 2.5Kg



10,000rpm, 1.7Kg







DH 45ME





180mm, Spindle Thread M14 x 2, 2,200W, 8,500rpm, 4.9Kg





